

High Power 680nm PM Optical Isolator

High Power 680nm Polarization Maintaining Optical Isolator is a fiber passive component built with TGG crystal, it allows light signal to be delivered in one forward direction and avoid the back reflection light, it's widely used in biomedical system, fiber optic sensor system to protect the light source and lower down the optical signal noise. The higher optical power is available up upon request, if need pulse type please contact us to confirm.

Application:

Optical Biomedical
Fiber Optic Sensor
Fiber Laser
Lab & Research

Features:

High Power
High Isolation
Low Insertion Loss
High Reliability



Specification:


Parameter	Symbol	Value	Unit
Center Wavelength	λ	680	nm
Bandwidth	BW	± 5	nm
Typ. Insertion Loss	IL	1.6	dB
Max. Insertion Loss	IL	2.0	dB
Typ. Peak Isolation	Iso	30	dB
Min. Isolation	Iso	22	dB
Min. Extinction Ratio for Fast Axis Blocked	ER	20	dB
Min. Extinction Ratio for Both Axes Working	ER	18	dB
Min. Return Loss	RL	45	dB
Max. Optical Power (CW)	P	0.5, 1, 2 or specify	W
Max. Peak Power	P	5 or specify	KW
Max. Tensile Load		5	N
Fiber Type		PM Panda Fiber	-
Operating Temperature	T	+10~50	°C
Storage Temperature	T	0~60	°C
Package Dimension			mm

Notice: Above specifications are tested at center wavelength without connector in room temperature @23°C.

For devices with connectors, IL will be 0.3dB higher, RL will be 5dB lower. ER will be 2dB lower.

Slow axis is default aligned to the connector key. Connectors only 1W CW optical power guarantee.

Drawing:



Ordering Information (Part Number):

HPMISO-**WWW**-**A**-**HH**-**J**-**LL**-**CC**

WWW	A	HH	J	LL	CC
Wavelength	Working Axis	Handling Power	Fiber Jacket	Fiber Length	Connector
488 - 488nm	F - Fast axis Blocked Slow Axis working	Z5 - 0.5W	B - 250um Bare Fiber 9 - 900um Loose Tube	05 - 0.5m	NE - None
532 - 532nm		01 - 1W		10 - 1.0m	FA - FC/APC
633 - 633nm	B - Both Axes Working	02 - 2W		15 - 1.5m	FU - FC/UPC
635 - 635nm		SS - Specify		20 - 2.0m	SA - SC/APC
650 - 650nm				SS - Specify	SU - SU/APC
680 - 680nm					LA - LC/APC
SSS - Specify					LU - LC/UPC
					SS - Specify