

1310nm SM Manual Variable Optical Attenuator

1310nm SM Manual Variable Optical Attenuator is a fiber component which can control the attenuation of the optical power by adjusting the screw, the attenuation value can be up to 60dB, it's widely used in optical power testing system, fiber line protection and optical power monitoring field.

Application:

Optical Power Monitoring
Fiber Line Protection
Testing System
Lab And Research

Features:

Low Original Loss
High Return Loss
High Attenuation Range
High Reliability




Specification:

Parameter	Symbol	Value	Unit
Center Wavelength	λ	1310	nm
Bandwidth	BW	± 40	nm
Attenuation Range		0.6-60	dB
Max. Original Loss	IL	0.6	dB
Adjustment Precision		0.02	dB
Max. Polarization Dependent Loss	PDL	0.1	dB
Min. Return Loss	RL	50	dB
Max. Optical Power (CW)	P	500	mW
Max. Tensile Load		5	N
Fiber Type		SMF-28e fiber	-
Operating Temperature	T	-5~70	°C
Storage Temperature	T	-40~85	°C
Package Dimension		26x18x8	mm

Notice: Above specifications are tested at center wavelength without connector in room temperature @23°C.

For devices with connectors, IL will be 0.3dB higher, RL will be 5dB lower.

Drawing:



Ordering Information (Part Number):

SMVOA- WWW - FF - J - LL - CC				
WWW	FF	J	LL	CC
Wavelength	Fiber Type	Fiber Jacket	Fiber Length	Connector
1310 - 1310nm	S2 - SMF-28e	B - 250um Bare Fiber	05 - 0.5m	NE - None
1450 - 1450nm	SS - Specify	9 - 900um Loose Tube	10 - 1.0m	FA - FC/APC
1480 - 1480nm		2 - 2.0mm Loose Tube	15 - 1.5m	FU - FC/UPC
1550 - 1550nm		3 - 3.0mm Loose Tube	20 - 2.0m	SA - SC/APC
1590 - 1590nm			SS - Specify	SU - SU/APC
1625 - 1625nm				LA - LC/APC
1650 - 1650nm				LU - LC/UPC
				SS - Specify